

Environmental & Health Datasheet

Self-declaration according to ISO 14021

EGGER Comfort Flooring

EGGER Comfort Flooring is a decorative multi modular floorcovering with integrated cork layers for residential and commercial interior usage. The cork layers are responsible for the characteristic properties: an elastic and warm feeling of the flooring. The material consumption of wood and cork combined with a digital printed decor provides a sustainable and ecological product which is available in various textures, designs and formats.



Raw Materials & Primary Products

Wood origin

Our plants are certified according to the standard ISO 38200:2018, wood can be referred to the ISO 38200: 2018 statements. On request and in agreement with your contact person at the EGGER sales department, our products can be declared on our sales documents also with other certification claims, depending on the availability at the production site. Please inquire availability details from your sales contact.

For certificates and an up-to-date list of the regional origin and wood species used in the product, see document available for download at www.egger.com/environment:

- Manufacturer's Declaration – Timber origins (Pdf)
- Certificate ISO 38200:2018 (Pdf)
- Further 3rd party certificates of sustainable wood procurement (Pdf)

Renewable content

	Renewable content	Fossil-based content
EGGER Comfort Flooring	87%	13%

Average renewable resource content by dry weight, in relation to all constituent materials (incl. wood, glue and others). Figures may vary between thicknesses.

Recycled content

	Virgin material	Co-products	Preconsumer recycling material	Postconsumer recycling material
EGGER Comfort Flooring	48%	52%	0%	0%

Average recycling content by dry weight, in relation to all constituent materials (incl. wood, glue and others). Figures may vary between thicknesses.

Responsible	Editor	Valid until	Revision	Classification	Page
Hüls Jörg	Bender Martina	07.01.2021	1.1	Public	1 of 13

Constituent materials

All chemicals have been evaluated and are disclosed down to 100 ppm. The table below contains 99.99 % of the primary products, measured by dry weight. Proportions may vary between individual product thicknesses. Listed is the average across all thicknesses in one production year.

Proportion	Function	Composition/ Add. info
72	% Dry wood fibers (HDF core board)	Industrial round wood, Saw mill by-products, Pre-consumer recycling wood and Post-consumer recycling wood
10	% Glue (HDF core board)	Urea-Melamine-Formaldehyde Glue (UMF) <i>During the pressing process, the aminoplastic adhesive hardens fully. Under normal conditions , it is bound to the wood and chemically stable.</i>
12.5	% Insulating cork layer (upside and bottom)	Cork granules (17% pre-consumer recycled, 83% virgin)
< 1	% Glue (cork sheet)	Melamine-Urea-glue (MUF) <i>During the production process, the aminoplastic adhesive hardens fully. Under normal conditions , it is bound to the wood and chemically stable.</i>
< 1	% Hydrophobing agent (core board)	Paraffine wax emulsion
< 1	% Formaldehyde scavenger (core board)	Technical Urea
< 1	% Surface protection layer	Acrylate-based UV lacquer (UV radiation-curing preparation)
< 1	% Glue (HDF-cork sandwich)	PUR hotmelt <i>The aminoplastic adhesive hardens fully. Under normal conditions , it is chemically stable.</i>
< 1	% Primer (between cork and decorative layer)	Acrylate-based UV lacquer (UV radiation-curing preparation)
< 0.1	% Decorative layer	Acrylate-based UV ink (UV radiation-curing preparation)

Manufacturing

Production plants & their certifications

The product is manufactured at the following location. For address and certification details, kindly see footnotes at the end of this document. Certifications are available for download at www.egger.com/environment.

Plant ⁱ	Certifications obtained by this plant			
	Quality	Environment	Energy	Wood origin
Wismar, Germany	ISO 9001	ISO 14001	ISO 50001	ISO 32800

Processing

Safety

This product is not hazardous in the form in which it is shipped by the manufacturer. Downstream activities (e.g. grinding, sanding, cutting or pulverizing) may generate wood dust, which is hazardous. Wear a respiratory mask if using hand tools without a dust extraction device. Observe all liability insurance association regulations for commercial processing operations (e.g. safety goggles).

Processing waste

Processing waste should be routed to an energetic recovery, due to its high calorific value. Upon incineration, observe all locally applicable legal requirements. Contact local authorities for details.

Calorific value: approx. 17.6 MJ/kg

Processing instructions

Please find comprehensive information (video and pdf) on the installation of the product available for download at www.egger.com/flooring.

Technical data

See technical datasheets available on flooring downloads at www.egger.com

Use

Product certification

On request, the product can be labelled with a certification claim according to:

- ISO 38200:2018
- Further 3rd party certificates of sustainable wood procurement

The product is certifiedⁱ according to:

- Blue Angel RAL UZ 176
- TÜV ProfiCert Product Interior PREMIUM
- M1
- A+ (French VOC emission class)
- Greenguard Gold

To download certificates, see flooring downloads at www.egger.com

Product emissions & Health aspects

During the raw board's manufacturing processes, heat and pressure is applied in a short cycle press. All resins cure completely into a solid material. In the use phase, the product is chemically stable under normal conditions. There are no known health hazards or health effects to be expected under normal conditions, when the product is used as intended.

The following table contains an overview of test results. The product is subjected to annual tests within the scope of TÜV PROFICERT-product Interior surveillance by an independent third party.

Substance / indicator	Product has been tested and fulfils emission requirement	Requirement	Requirement details ⁱⁱⁱ
Formaldehyde	✓	E1	Formaldehyde class E1, according to EN 13986+A1:2015-04
Formaldehyde	✓	E1 (Germany) ≙ E1E05	German ChemVerbotsVO Formaldehyde class E1 from 1.1.2020, external testing
Formaldehyde	✓	TSCA	U.S. Toxic Substances Control Act
Formaldehyde	✓	CARB P2	California's Composite Wood Products Regulation
VOC, Formaldehyde, Carcinogens, Ammonia, Nitrosamines	✓	TÜV PROFICERT-product Interior PREMIUM	Common Label for the Health and Quality Assessment of Interior Products
VOC, Carcinogens	✓	AgBB, February 2015	via TÜV PROFICERT (see above)
VOC	✓	French VOC regulation, emission class A+	via TÜV PROFICERT (see above)
VOC, Nitrosamines, Ammonia	✓	German MVV TB ABG Annex 8	via TÜV PROFICERT (see above)
VOC	✓	Belgian VOC regulation	via TÜV PROFICERT (see above)
VOC, Formaldehyde, Carcinogens	✓	BREEAM International New Construction 2016	via TÜV PROFICERT (see above)
Formaldehyde, VOC, TSVOC, Ammonia, Carcinogens	✓	German Ecolabel RAL UZ 176	via TÜV PROFICERT (see above)
TVOC, Formaldehyde, Ammonia, Carcinogens	✓	Finnish Emission Classification of building materials M1	via TÜV PROFICERT (see above)
Formaldehyde	✓	LEED v4 (outside North America)	via TÜV PROFICERT (see above)
VOC, Odorous substances, Irritants	✓	Austrian Ecolabel UZ 56	via TÜV PROFICERT (see above)

Cleaning & Maintenance

Please find comprehensive information on the care, maintenance, and repair of the product available for download at www.egger.com/flooring.

End of life – waste treatment

Maintenance

To maintain the product properties and extend the use phase as long as possible, see document available for download at www.egger.com

- Guarantee declaration and care instructions for Egger Comfort Flooring

Reuse

In case of careful deconstruction and proper storage, reuse is possible for the same application. Product may not be bonded over its entire back side or along the profiles, in case of a desired reuse. Special care must be taken when disassembling the floor to keep the profiles intact.

Recycling – material use

Material recovery is not possible with current technology, in practice.

Incineration – energetic use

Product should be collected separately and routed to an energetic recovery, due to its high calorific value. Upon incineration, observe all locally applicable legal requirements. Contact local authorities for details.

Calorific value: approx. 17.6 MJ/kg

Disposal

The product is not classified as hazardous waste.

Compliance with LEED v4

EGGER Comfort Flooring is compliant with the prerequisites for use in LEED certified buildings. Beyond that the usage of EGGER Comfort Flooring contributes to gather additional points within the LEED scoring system. The following table shows all LEED credits which are applicable to the usage of our product. As the actually achievable number of points depends on the attributes of all used materials in the LEED building project and further actions by the constructor, we cannot guarantee to obtain the maximum score. For full requirement terms see LEED credit library at www.usbc.org.

Projects outside U.S.

LEED v4 Requirements for Building Design + Construction (BD+C) New Construction, Core and Shell, Schools, Retail, Healthcare, Data Centers, Hospitality, Warehouses and Distribution Centers			Product contributions
LEED v4 Requirements for Interior Design + Construction (ID+C) Commercial Interiors, Retail, Hospitality			
Chapter	Requirement summary	Maximum Points	
Material and Resources	Building Product Disclosure and Optimization - Environmental Product Declarations Option 1. Environmental Product Declaration (EPD)	0 Points	Currently, this product has no EPD.
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 1.:Raw material source and extraction reporting Third-party verified corporate sustainability reports (CSR) according to an accepted framework.	2 Point	An annual Sustainability report is published in accordance with the GRI standards: "Core" option, and is audited by an independent party. See <ul style="list-style-type: none"> Sustainability report (Pdf) available for download at www.egger.com/environment .
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 2.3: Wood products must be certified by the Forest Stewardship Council or USGBC-approved equivalent.		
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 2.5: Recycled content is the sum of postconsumer recycled content plus one half the pre-consumer recycled content, based on cost.		
Material and Resources	Building Product Disclosure and Optimization - Material Ingredients Option 1: Declare.	1 Point	The manufacturer has screened the product to at least 1,000 ppm and has provided a publicly available inventory. See "Constituent materials" section above to obtain further information.
Indor Environmental Quality	Low-emitting Materials- VOC emissions evaluation Product complies with the LCI values of the German AgBB Testing and Evaluation Scheme	3 Points	Product complies with the LCI values of the German AgBB scheme. See "Product emissions & Health aspects" section above for further information. Use <ul style="list-style-type: none"> TÜV ProfiCert Product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads .

Projects inside U.S.

Please note that VOC testing requirements in LEED v4 are deviating for projects **inside the U.S.**

LEED v4 Requirements for Building Design + Construction (BD+C) New Construction, Core and Shell, Schools, Retail, Healthcare, Data Centers, Hospitality, Warehouses and Distribution Centers			Product contributions
LEED v4 Requirements for Interior Design + Construction (ID+C) Commercial Interiors, Retail, Hospitality			
Chapter	Requirement summary	Maximum Points	
Material and Resources	Building Product Disclosure and Optimization - Environmental Product Declarations Option 1. Environmental Product Declaration (EPD)	0 Points	Currently, this product has no EPD.
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 2.3: Wood products must be certified by the Forest Stewardship Council or USGBC-approved equivalent.	1 Point	The products is verified by the ISO 38200 : 2018 statements. Additionally, the product can be purchased in other certified qualities on request. Use delivery receipt as evidence document. See also chapter "Wood origin" of this document.
Material and Resources	Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 2.5: Recycled content is the sum of postconsumer recycled content plus one-half the pre-consumer recycled content, based on cost.		Recycled content of the product (based on weight) = 0% + 52%/2 =26% . See "Constituent materials" section above to obtain further information.
Material and Resources	Building Product Disclosure and Optimization - Material Ingredients Option 1: Declare.	1 Point	The manufacturer has screened the product to at least 1,000 ppm and has provided a publicly available inventory. See "Constituent materials" section above to obtain further information.
Indoor Environmental Quality	Low-emitting Materials- VOC emissions evaluation Building products must be tested and determined compliant in accordance with California Department of Public Health (CDPH) Standard Method v1.1–2010	3 Points	Range of total VOC measured as specified in the CDPH Standard Method <0.5 mg/m ³ . See "Product emissions & Health aspects" section above for further information. Use <ul style="list-style-type: none"> ▪ UL Greenguard Gold certificate as evidence document, available for download at www.egger.com/downloads .

Compliance with WELL Building Standard v2™

EGGER EGGER Comfort Flooring is compliant with the preconditions for use in WELL v2™ certified buildings. Beyond that the usage of this product may contribute to gather additional points within the WELL scoring system. The following table shows all WELL features which are applicable to the usage of our product. As the actually achievable number of points depends on the attributes of all used materials in the WELL building project and further actions by the constructor, we cannot guarantee to obtain the maximum score. For full requirement terms see WELL feature library at www.wellcertified.com.

Chapter	Requirements		Product contributions
	Requirement summary	Maximum Points	
X01 Material Precautions	Restrict asbestos, mercury and lead.	Precondition	The product complies with this precautions. See Manufacturer's Declaration – Asbestos (Pdf) available for download at www.egger.com/environment . Please get in touch with the EGGER product sustainability & compliance team at environment@egger.com to get further declarations concerning the non-use of mercury and lead .
X05 Enhanced Material Restrictions	Part 2a Select Compliant Architectural and Interior Products: Ceiling and wall panels contain halogenated flame retardants (HFR) at less than 100 ppm.	1 Point	The product complies with this requirement. No halogenated flame retardants (HFR) are used in this product. See "Constituent materials" section above for your documentation. Please get in touch with the EGGER product sustainability & compliance team at environment@egger.com to get Manufacturer's declaration on the use of halogenated compounds (Pdf).
X05 Enhanced Material Restrictions	Part 2a Select Compliant Architectural and Interior Products: Newly installed floorings and furniture contain Orthophthalates at less than 100 ppm.		The product complies with this requirement. No phthalates are used in the product. See "Constituent materials" section above for your documentation.
X05 Enhanced Material Restrictions	Part 2a Select Compliant Architectural and Interior Products: Flooring products contain Polyfluoroalkyl substances (PFAS) at less than 100 ppm.		The product complies with this requirement. No CMR substances are added to the product at all. Use <ul style="list-style-type: none"> ▪ TÜV ProfiCert Product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads .
X06 Volatile Compound reduction	Part 2a Restrict VOC Emissions from Furniture, Architectural and Interior Products: Furniture and wall panels tested per AgBB or CDPH method and VOC emission threshold established.	2 Points	Product complies with the LCI values of the German AgBB scheme. See "Product emissions & Health aspects" section above for further information. Use <ul style="list-style-type: none"> ▪ TÜV ProfiCert Product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads .
X06 Volatile Compound reduction	Part 2c2 Restrict VOC Emissions from Furniture, Architectural and Interior Products: Composite wood panels meet the formaldehyde standards European E1, TSCA, F*** or LEED v4.1		Product is tested per EN 717-1:2014 for formaldehyde emissions and complies with emissions class E1. Use <ul style="list-style-type: none"> ▪ TÜV ProfiCert Product Interior PREMIUM as evidence document, available for download at www.egger.com/downloads .
X07 Material Transparency	Part 1: Select Products with Disclosed Ingredients: Promote ingredient disclosure with ingredients identified and disclosed to 1,000 ppm.		The product is screened to at least 1,000 ppm and the manufacturer has provided a publicly available inventory within this document. See "Constituent materials" section above for your documentation.

Compliance with BREEAM International New Construction 2016

EGGER Comfort Flooring is compliant with the preconditions for use in BREEAM 2016 certified buildings and fulfils the emission requirements at exemplary level. Beyond that the usage of this product may contribute to gather additional points within the BREEAM scoring system. The following table shows all BREEAM credits which are applicable to the usage of our product. As the actually achievable number of credits depends on the attributes of all used materials in the BREEAM building project and further actions by the constructor, we cannot guarantee to obtain the maximum score. For full requirement terms see BREEAM manual at www.breeam.com.

Requirements			Product contributions
Chapter	Requirement summary	Maximum Credits	
Mat 01 Life cycle impacts	<i>Environmental product declarations (EPD) – product installed by Post-Construction Stage is covered by verified EPD</i>	0 Credits	<i>Currently, this product has no EPD.</i>
Mat 03 Responsible sourcing of construction products	All timber-based products used on the project are Legally harvested and traded timber.	Prerequisite	The products is verified by the ISO 38200 : 2018 statements. This standard takes into account all legal requirements in the respective purchasing or production country and all environmental and social criteria known in the ISO system. Additionally, the product can be purchased in other certified qualities on request. Use delivery receipt as evidence document. See also chapter “Wood origin” of this document.
Hea 02 Indoor air quality	Avoidance of asbestos.	Prerequisite	The product complies with this prerequisite. See <ul style="list-style-type: none"> ▪ Manufacturer’s Declaration – Asbestos (Pdf) available for download at www.egger.com/environment
Hea 02 Indoor air quality	Minimising sources of pollution - Emissions from building products. Product should meet the exemplary level emission criteria Formaldehyde ≤ 0.06 mg/m ³ TVOC ≤ 1.0 mg/m ³ Category 1A and 1B carcinogens ≤ 0.001 mg/m ³	1 Credit	Product meets the exemplary level emissions criteria. Use <ul style="list-style-type: none"> ▪ TÜV ProfiCert Product Interior Premium as evidence document, available for download at www.egger.com/downloads .

Compliance with DGNB Gebäude Neubau 2018

As the DGNB certification system is primarily relevant for projects in the German-speaking countries, this chapter is given in German language.

Die DGNB Auszeichnungen Silber, Gold und Platin ergeben sich aus den Gesamterfüllungsgrad des Bauprojektes. Welche Qualitätsstufen das Produkt EGGER Comfort Flooring nach dem DGNB-System erfüllt und wo Sie die benötigten Nachweise finden, können Sie der folgenden Tabelle entnehmen. Die Beiträge zum Gesamterfüllungsgrad, die sich nach dem DGNB Punktesystem hieraus ergeben, hängen u.a. von der Relevanz der Produktgruppe für das Gesamtgebäude ab. Bitte beachten Sie, dass für die Gesamtbewertung des Gebäudes darüber hinaus noch weitere Kriterien von Bedeutung sind. Eine durch den Einsatz des Produktes EGGER Comfort Flooring zu erhaltende Punktzahl können wir daher nicht garantieren.

Kriterien			Beitrag des Produktes
Themenfeld	Zusammenfassung Kriterium	Qualitätsstufe/ Bonus	
ENV1.1 Ökobilanz des Gebäudes	<i>Die Gebäude-Ökobilanz benötigt Baustoffdaten. Produktspezifische Daten (EPDs) werden bevorzugt.</i>	-	<i>Für das Produkt liegt derzeit keine Umweltproduktdeklaration (EPD) vor.</i>
ENV1.2 Risiken für die lokale Umwelt	Formaldehydgrenzwert für Holzwerkstoffe in Aufenthaltsräumen: RAL UZ 76 oder Formaldehyd <0,05 ppm in Prüfkammer.	4	Der Grenzwert wird eingehalten. Nutzen Sie das TÜV PROFICERT-Zertifikat als Nachweis. Sie finden das Dokument <ul style="list-style-type: none"> ▪ TÜV ProfiCert Product Interior Premium im Downloadbereich auf www.egger.com/umwelt .
ENV1.3 Verantwortungsvolle Ressourcengewinnung	Zertifizierte verantwortungsbewusste Ressourcengewinnung eines Teils der Wertschöpfungskette.	1.2	Die Lieferkette von Holz und Papier sind nach ISO 38200 (Chain-of-Custody, CoC) zertifiziert. Die Norm berücksichtigt alle Legalitätsanforderungen im jeweiligen Einkaufs- bzw. Produktionsland und alle im ISO System bekannten Umwelt- und Sozialkriterien. Sie finden das Dokument <ul style="list-style-type: none"> ▪ Herstellererklärung über die Holzherkünfte (Pdf) im Downloadbereich auf www.egger.com/umwelt .

Compliance with Nordic Swan Ecolabel

Small houses, apartment buildings and buildings for schools and pre-schools

The product EGGER Comfort Flooring is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings (Portal Nordic Ecolabelling) under the Manufacturer's name Egger, Fritz GmbH & Co. As an applicant for an Ecolabelled building, please inform your Nordic Swan certifier about the product listing. For the use of EGGER Comfort Flooring no other documents are necessary for your application.

Compliance with other labels & regulations

Additional information in the form of manufacturer declarations, EPDs and brochures is available at

- www.egger.com/environment

Your label or regulation is missing? The EGGER product sustainability & compliance team is happy to support you with suitable information on the requirements. Please get in touch with

- environment@egger.com

or contact your EGGER sales contact or distributor, who are happy to forward the inquiry.

Footnotes

i

Production plant	Address
Wismar, Germany	EGGER Holzwerkstoffe GmbH & Co. KG, Am Haffeld 1, 23970 Wismar (D)

ii

Product Certifications	
ISO 38200	ISO 38200:2018 Chain of Custody of wood and wood-based products
Blue Angel	German Ecolabel RAL UZ 176 (2013)
TÜV ProfiCert Product Interior PREMIUM	TÜV PROFICERT-product Interior certification criteria V1.1
M1	M1 Emission Classification of Building Materials: Protocol for Chemical and Sensory Testing of Building Materials
A+	VOC emission class according French VOC regulation (Arrêté du 19 avril 2011 relatif à l'étiquetage des produits de construction ou de revêtement de mur ou de sol et des peintures et vernis sur leurs émissions de polluants volatils)
Greenguard Gold	UL 2818 GGREENGUARD Standard for Building Materials, Finishes And Furnishings

iii

Substance	Norm	Limit value	Testing method	Accredited testing institute
Formaldehyde	According to EN 13986+A1:2015-04, Formaldehyde class E1	0.1 ppm	EN 717-1	EPH Entwicklungs- und Prüflabor Holztechnologie GmbH, Dresden (Germany)
Formaldehyde	TSCA/ CARB P2	0.11 ppm	ASTM E1333-14	EPH Entwicklungs- und Prüflabor Holztechnologie GmbH, Dresden (Germany)
<ul style="list-style-type: none"> ▪ TVOC ▪ TSVOC ▪ VOC ▪ R value ▪ Formaldehyde ▪ Acetaldehyde ▪ Toluol ▪ 1,4 Dichlorobenzene ▪ Trichlorethylene ▪ Tetrachlorethylene ▪ Xylol ▪ Styrol ▪ DEHP ▪ DBP ▪ Carcinogenic, mutagenic substances and substances toxic to reproduction (EU-category 1A and 1B according to CLP Regulation (EC) No 1272/2008) ▪ Ammonia ▪ Nitrosamines 	TÜV PROFICERT-product Interior PREMIUM v 1.1 for details see proficert.de	160 µg/ m ³ (28d) 100 µg/ m ³ (28d) 100 µg/ m ³ (28d) 1 10 µg/ m ³ (28d) 200 µg/ m ³ (28d) 300 µg/ m ³ (28d) 60 µg/ m ³ (28d) 1 µg/ m ³ (28d) 350 µg/ m ³ (28d) 300 µg/ m ³ (28d) 350 µg/ m ³ (28d) 1 µg/ m ³ (28d) 1 µg/ m ³ (28d) 1 µg/ m ³ each (28d)	ISO 16000 part 6/ EN 16516	TÜV Hessen, Darmstadt (Germany)
<ul style="list-style-type: none"> ▪ VOC ▪ Carcinogens 	German AgBB	see TÜV PROFICERT	see TÜV PROFICERT	covered by TÜV PROFICERT-product Interior PREMIUM
VOC	French A+	see TÜV PROFICERT	see TÜV PROFICERT	covered by TÜV PROFICERT-product Interior PREMIUM
VOC	Belgian VOC regulation	see TÜV PROFICERT	see TÜV PROFICERT	covered by TÜV PROFICERT-product Interior PREMIUM
<ul style="list-style-type: none"> ▪ VOC ▪ Nitrosamines ▪ Ammonia 	German MVV TB / ABG Annex 8	see TÜV PROFICERT	see TÜV PROFICERT	covered by TÜV PROFICERT-product Interior PREMIUM
<ul style="list-style-type: none"> ▪ VOC ▪ Formaldehyde ▪ Carcinogenes 	BREEAM International, Exemplary Level	see TÜV PROFICERT	see TÜV PROFICERT	covered by TÜV PROFICERT-product Interior PREMIUM
<ul style="list-style-type: none"> ▪ Formaldehyde ▪ VOC ▪ TSVOC ▪ Ammonia ▪ Carcinogens 	German Ecolabel RAL UZ 176	see TÜV PROFICERT	see TÜV PROFICERT	covered by TÜV PROFICERT-product Interior PREMIUM
<ul style="list-style-type: none"> ▪ TVOC ▪ Formaldehyde 	Finnish M1	see TÜV PROFICERT	see TÜV PROFICERT	covered by TÜV PROFICERT-product Interior PREMIUM

Core Material Management & Product Sustainability

<ul style="list-style-type: none"> ▪ Ammonia ▪ Carcinogens 				
<ul style="list-style-type: none"> ▪ Formaldehyde ▪ VOC 	LEED v4 outside North America	see TÜV PROFICERT	see TÜV PROFICERT	covered by TÜV PROFICERT-product Interior PREMIUM
<ul style="list-style-type: none"> ▪ VOC ▪ Odorous substances ▪ Irritants 	Austrian Ecolabel UZ 56	see TÜV PROFICERT	see TÜV PROFICERT	covered by TÜV PROFICERT-product Interior PREMIUM