

PLANK FINELINE 14 mm Clic

Technical information:

| | | |
|--|--|------------------------|
| Produced according to: | European parquet norm EN 13489 - 2017 | |
| Dimension: | 14 x 138 x 2200 mm | |
| Toplayer: | ca. 3.5 mm | |
| Construction: | 3-layer construction; Hardwood toplayer, middlelayer and bottomlayer made of spruce Toplayer about 3.5 mm Middlelayer 8.8 mm Bottomlayer 1.7 mm | |
| Boards / m² per carton: | 10/ 3.04 | |
| Cartons/ m² per pallet: | 42/ 127.68 | |
| Slotted top layers per carton/ minimum length (mm): | - | |
| Weight per carton/ pallet in kg: | 25.5/ 1071 | |
| Floor heating systems: | Well suitable to very well suitable | |
| Fire behavior ¹⁾: | Cfl-s1 and Dfl-s1 depending on wood specie and surface treatment | |
| Content of formaldehyd ²⁾: | E1 | |
| Content of pentachlorophenol (PCP) ²⁾: | non performance detected | |
| Density kg/ m³ ²⁾: | about 600 | |
| Antislip performance: | Live Satin | USRV 25 ²⁾ |
| | Live Matt | USRV 29 ²⁾ |
| | Live Natural | USRV 40 ²⁾ |
| Abrasion resistance: | Live Satin | 70/ 1100 ³⁾ |
| | Live Satin | 100 ⁴⁾ |
| Thermal conductivity ²⁾: | 0.15 W/ (m·K) | |
| Areal thermal resistance ⁵⁾: | 0.093 m ² · K/ W | |



BOEN AS
EN 14342
DOP 4658



www.blauer-engel.de/uz176



¹⁾ according to DIN EN 13501-1, ²⁾ according to DIN 14342, ³⁾ according to ENV 13696, ⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524